



LIFTKET B13, B15 & POWER LIFTKET



24 V AC Low Voltage Control



Up to 25.000kg load capacity



Available in 1 and 2 falls



Available with suspension eye,
hook suspension (B13) or electric trolley

Maßgeschneiderte Elektrokettenzüge mit
extrem hohen Traglasten | Customized electric
chain hoists with extremely high load capacities

MADE IN GERMANY

LIFTKET B13, B15 & POWER LIFTKET

Unsere Elektrokettenzüge mit extrem hohen Traglasten
Our electric chain hoists with extremely high load capacities

- Traglasten bis zu 25.000 kg möglich | Up to 25.000 kg load capacity possible
- Bewährte hohe Qualität "Made in Germany" | Approved high quality "Made in Germany"
- Simple Handhabung und geringer Wartungsaufwand | Simple handling and low maintenance
- Umrüstung von ein- auf zweisträngigen Betrieb und umgekehrt | Upgrade from single to double fall operation and backwards
- Erhältlich mit Aufhängeöse, Hakenaufhängung (B13) oder Elektrofahrwerk | Available with suspension eye, hook suspension (B13) or electric trolley



Ausstattung und Modellvarianten Equipment and models variants:

4.000 - 25.000 kgs
380 - 415 V, 50 Hz, IP55
Komplett mit 3 m Hubhöhe |
incl. 3 m lifting height
1,5 m Steuerkabel | 1.5 m control cable
Hängetaster mit NOT-HALT | control
pendant with emergency stop
Schützsteuerung 24 V AC |
low voltage control 24 V AC
Temperaturwächter für Hubmotor | Thermal
protection for lifting motor
Getriebeentschalter 4-spurig |
gear limit switch 4-traced

	ISO	Type		EN818-7 DAT	
					
kg				mm	m/min
4.000	M5	4000/1-5,6/1,4	B13/00X	16 x 45	5,6 / 1,4
5.000	M4	5000/1-5,6/1,4	B13/00X	16 x 45	5,6 / 1,4
6.300	M3	6300/1-5,6/1,4	B13/00X	16 x 45	5,6 / 1,4
7.500	M3	7500/1-4,4/1,1	B15/00Y	17,3 x 48	4,4 / 1,1
8.000	M5	8000/2-2,8/0,7	B13/00X	16 x 45	2,8 / 0,7
		8000/1-6,4/1,6	235/50	23,5 x 66	6,4 / 1,6
10.000	M4	10000/2-2,8/0,7	B13/00X	16 x 45	2,8 / 0,7
		10000/1-6,4/1,6	235/50	23,5 x 66	6,4 / 1,6
12.500	M3	12500/2-2,8/0,7	B13/00X	16 x 45	2,8 / 0,7
		12500/1-6,4/1,6	235/50	23,5 x 66	6,4 / 1,6
15.000	M3	15000/2-2,2/0,6	B15/00Y	17,3 x 48	2,2 / 0,6
16.000	M5	16000/2-3,2/0,8	235/50	23,5 x 66	3,2 / 0,8
20.000	M4	20000/2-3,2/0,8	235/50	23,5 x 66	3,2 / 0,8
25.000	M3	25000/2-3,2/0,8	235/50	23,5 x 66	3,2 / 0,8

* Andere Spannungen und Frequenzen auf Anfrage möglich |
Other voltages and frequencies are available on request