

Rollenbock DSRB S für Drahtseilumlenkung, kugelgelagert

für händisch und motorisch betriebene Winden

Typ	Triebwerksgruppe	Seilzuglast bei Umlenkung 90°	Seilzuglast bei Umlenkung 180°	Seildurchmesser	Art.-Nr.	Preis pro Stück
	FEM/ISO	kg	kg	mm		Euro
DSRB S 90/4	2m/M5	700	500	3-4	33447103	95,00
DSRB S 90/6	1Dm/M1	700	500	5-6	33447413	121,00
DSRB S 145/5	4m/M6	1.100	800	5	33447104	156,00
DSRB S 145/6	2m/M5	1.100	800	6	33447105	152,00
DSRB S 145/7	1m/M4	1.100	800	7	33447106	175,00
DSRB S 185/8	2m/M5	2.300	1.630	8	33447107	236,00
DSRB S 185/9	1Am/M4	2.300	1.630	9	33447108	252,00
DSRB S 270/12	2m/M5	2.500	1.800	9-12	33447111	484,00



DSRB S Abmessungen

Typ	Abmessungen in mm										
	B	C	ØD	ØD1	ØDm	E	H	K	L	ØM/M1	S
DSRB S 90/4	85	90	90	20	80	62	134	65	120	9/9	4
DSRB S 90/6	85	90	90	25	78	62	134	65	120	9/9	6
DSRB S 145/5	125	160	145	25	125	88	224	110	200	11,5/13	6
DSRB S 145/6	125	160	145	25	125	88	224	110	200	11,5/13	6
DSRB S 145/7	125	160	145	25	126	88	224	110	200	11,5/13	6
DSRB S 185/8	138	195	185	30	160	106	273	135	245	13,5/15	8
DSRB S 185/9	138	195	185	30	162	106	273	135	245	13,5/15	8
DSRB S 270/12	191	290	270	40	246	138	407	202	360	18/20	10

