

## APPLICATIONS

The HT42 harness is simple to use and easy to adjust. It is designed for all operations where the operator needs to use the fall arrest from the front (roofer, ladder work).

Its 2 front attachment points ensure great versatility.

It is possible to connect an adjustable EN 358 lanyard between the two thoracic attachment points for short-term use, but a fall arrester must always be used together in this configuration.

This harness is ideal for industrial maintenance work.



## TECHNICAL CHARACTERISTICS

- 1 back attachment point, 2 thoracic attachment points.
- Quick adjustment of the shoulder straps with sliding bar buckle.
- Flat buckles for fastening and adjusting the straps.
- Loops for holding the leg straps and the shoulder straps.
- Under-buttock strap.
- Sewn-in anti-release stops at the ends of the straps
- Maximum working load (operator and equipment): 150 kg
- Available sizes: S, M, XL.
- Weight (Size M): 1090 g.
- Polyester webbing.
- Polyester stitching threads.
- Cataphoresis treated steel buckles.
- Option:
  - Work positioning belt.
  - X-PAD.

## APPLICABLE STANDARDS

- EN 361.

## STANDARD PRODUCTS

Code	Description	Weight
031622	HT42 S	1040 g
010042	HT42 M	1090 g
031082	HT42 XL	1160 g

## LOGISTIC INFORMATION

Code	Description	EAN Code	Packaging size
031622	HT42 S	3600230316222	138 x 120 x 222
010042	HT42 M	3600230100425	138 x 120 x 222
031082	HT42 XL	3600230310824	138 x 120 x 222