

APPLICATION:

The HT44 harness is simple to use with easy adjustment, it is ideal for industrial maintenance interventions. HT44 harnesses are technical harnesses for the building and industrial markets. The HT44 harness is designed for all operations where the operator needs to use his fall arrester from the front. Their ergonomics ensure optimal comfort and are intended for long term work. The HT44 harness is widely used in the field of small interventions on pylons, in the field of electricity or telecommunications. Its 2 front attachment points make it very versatile. It is possible to connect an EN 358 adjustable lanyard between the two thoracic attachment points for short interventions, but it is imperative to have a fall arrest system when using it. It is equipped with mountain-type leg loops which optimise comfort and provide great mobility in the harness. The label holder allows the storage and recording of customer information.



TECHNICAL FEATURES:

- 1 Dorsal attachment.
- 2 Thoracic attachments.
- Quick adjustment of shoulder straps.
- Locking and adjustment of straps with flat buckles.
- Mountain-type leg loops.
- Elastomer loops on leg and shoulder straps.
- Thoracic strap with lateral adjustment.
- Buttock strap.
- Label holder.
- End stops against strap release.
- Maximum authorized weight (operator and equipment): 150 kg.
- Available sizes: S, M, XL.
- Weight (Size M): 1420 g.

OPTIONS:

- Work positioning belt
- X PAD

CE CERTIFICATION:

- Notified Body: Alienor certification CE2754
- N°: 2754/0352/160/10/20/0640

STANDARDS COMPLIANCE:

- EN 361

ASSOCIATED EQUIPMENT:

- EN 795 Anchorage system
- EN 362 Connectors
- EN 363 Fall arrest system

CODES:

DESIGNATION	CODE	EAN CODES
HT 44 S	44102	3600230441023
HT 44 M	44112	3600230441122
HT 44 XL	44122	3600230441221