

APPLICATION:

HT56 harnesses are technical harnesses for the construction and industrial markets. They are ergonomic and comfortable and are designed for long term work.

The HT56 harness is widely used for work on roofs, ladders and scaffolding.

The HT56 harness is designed for all operations where the operator needs to use his fall arrester from the front.

Its 3 front attachment points ensure it is highly versatile. It is possible to connect an EN 358 adjustable lanyard between the two thoracic attachment points for a short intervention, but it is imperative to have a fall arrest system for this use.

The sternal attachment point facilitates the handling of fall arresters on flexible anchor line and ensures better comfort at the workplace. The large-diameter dorsal attachment point makes it easier to hook a connector to the operator's back.

The HT56 harness is simple to use with easy adjustment, it is ideal for building interventions.

It is equipped with mountain-type leg loops which optimise comfort and provide great mobility in the harness. It is equipped with an X-PAD which increases comfort and distributes the weight of the harness over the operator's shoulders. It also makes it easier to put on the harness.

The label holder allows the storage and registration of customer information.



TECHNICAL FEATURES:

- 1 Dorsal attachment.
- 1 Sternal attachment.
- 2 Thoracic attachments.
- Quick adjustment of shoulder straps.
- Locking and adjustment of straps with flat buckles.
- Mountain-type leg loops.
- Elastomer loops on leg and shoulder straps.
- Thoracic strap with lateral adjustment.
- Buttock strap.
- Label holder.
- End stops against strap release.
- Maximum authorized weight (operator and equipment): 150 kg.
- Integrated fall indicator in straps.
- Available sizes: S, M, XL.
- Weight (Size M): 1850 g.

OPTIONS:

- Work positioning belt

CE CERTIFICATION:

- Notified Body: Alienor certification CE2754
- N°: 2754/0352/160/10/20/0648

STANDARDS COMPLIANCE:

- EN 361

ASSOCIATED EQUIPMENT:

- EN 795 Anchorage system
- EN 362 Connectors
- EN 363 Fall arrest system

CODES:

DESIGNATION	CODE	CODES EAN
HT 56 S	65302	3600230653020
HT 56 M	65312	3600230653129
HT 56 XL	65322	3600230653228