

APPLICATION

The work positioning lanyard LCM03 is a manually adjusted tensioner-reducer. This device works on a low-stretch rope with soul in steel diameter of 14mm and length of 2 to 4m. The LCM03 is compact and ergonomic and perfectly suited for work positioning.



TECHNICAL CHARACTERISTICS

- Tensioner made in aluminum
- Braided rope with soul in steel, diameter 14 mm
- Steel screw connector M10T, 17 mm opening
- Aluminium connector M42, 18mm opening or Steel connector M41, 17mm opening
- Strength 15kN
- Option Cut-resistant sheath, PA strap, 50 cm

DESCRIPTION

The lanyard LCM03 is equipped with a compact, ergonomic tensioner-reducer. The device is made of high-strength aluminium. The LCM03 is moved along the rope by simply pressing on the tensioner jaw. In the event of a fall or loss of balance, the tensioner automatically locks.

The unit is supplied with a low-stretch rope with soul in steel diameter of 14 mm and length of 2m, 3m or 4m, equipped with a connector M10T on the tensioner and a connector M41 or M42 on the end of the rope.

These are used to support the person who is working, these lanyard are not fall protection devices.

NORM

- Conforms to standard EN358.

CODES

DESIGNATION	CODE	EAN CODE
LCM03 41-10T DRISSE 150KG 2m	085262	3600230852621
LCM03 41-10T DRISSE 150KG 3m	085272	3600230852720
LCM03 41-10T DRISSE 150KG 4m	085282	3600230852829
LCM03 42-10T DRISSE 150KG 2m	085292	3600230852928
LCM03 42-10T DRISSE 150KG 3m	085302	3600230853024
LCM03 42-10T DRISSE 150KG 4m	085312	3600230853123