

APPLICATION

Work positioning belt. It must be used in combination with a work positioning lanyard.
This product is not suitable for protection against falls from a height. If there is a risk of falling, use a fall arrest system EN 363 in addition.
CE01 belts are available as flat buckles (CE01) and automatic buckles (CE01 A). They are connectable to fall arrest harnesses by the straps and assembly buckle. (fig 1)



COMPOSANTS ET CARACTERISTIQUES

- Lateral anchorage: two de ring of 45 mm (fig 2)
- Quick adjustment and opening by flat or automatic buckle (fig 3)
- Blue backrest in light foam and rot-proof on the outside, black terry fabric on the inside.
- Maximum operating load: 150 kg

MATIERE

- Strap : polyester
- Buckle : zinc steel

CERTIFICATION CE

- Notified body : ALIENOR CERTIFICATION CE 2754
- N° : 2754/0352/160/08/19/0820

MORMES

- EN 358 / 2018 – european norm

MODELE

Code	Désignation	Size	ean
032882	CE01 S	S	3600230328829
010052	CE01 M	M	3600230100524
010062	CE01 XL	XL	3600230100623
033202	CE01 SA	S	3600230332024
033212	CE01 MA	M	3600230332123
033222	CE01 XLA	XL	3600230332222

Tableau des tailles 20 11 2017

	S	M	XL	XXL	XXXL
A	60 - 100	80 - 120	100 - 160	130 - 170	-
B	75 - 100	90 - 110	100 - 150	130 - 170	-
C	45 - 60	45 - 70	45 - 80	80 - 90	-
D	55 - 65	65 - 80	80 - 90	90 - 100	-